

## DCW 001 3000K

Wall-mounted LED-based luminaire

### Description

Wall-mounted luminaire with direct illumination. Housing made of extruded anodized aluminum. DCW 001 has 1 LED – illumination is directed up or down depending on the installation method. DCW 002 has 2 LEDs – illumination is directed up and down. LEDs are covered with lenses made of polymeric material.

### Installation



On a wall.

### Design

Anodized extruded aluminum housing.

### Optical part

Polymeric lens.



## Dimensional characteristics

A	Length	75 mm
B	Width	30 mm
C	Height	75 mm
D	Length (mounting)	65 mm
	Weight	0.2 kg

## Technical features

1	Article no.	1539000010
2	Light source	LED
3	Luminous flux	75 lm
4	Power compatibility	1 W
5	Energy efficiency	75 lm/W
6	Color rendering index (CRI)	>80
7	Color temperature	3000 K
8	Power factor (cosFI)	> 0,50
9	Alternating/direct current (AC/DC)	No
10	Dimming	-
11	Rated voltage	230 V
12	Electrical shock protection	I
13	Electromagnetic compatibility (EMC)	Yes
14	Climate application	CIm App4
15	Ambient temperature	+5 to +35 C
16	Housing color	Silver
17	Fire protection class	III
18	Flickering	<5%
19	Ingress protection (IP)	IP20
20	Mechanical shock protection	IK02/0,2 J
21	Energy efficiency class	A++
22	Inrush current	-
23	Inrush current impulse time	0 µs
24	Emergency power supply unit	No
25	Beam angle	D120
26	Warranty	60 months
27	Autonomy in emergency mode	-
28	Light flux in emergency mode	-