

EMERGENCY CONVERSION KIT LED K-501 SLICK



Emergency power unit

Description


Used in LED- or traditional lamp-based in case of a sudden mains power supply failure. Supplied as a kit comprising the following: emergency power supply unit, charge indicator (green LED), Ni-Mg battery, TEST button (for emergency mode operation check, installed inside the box), emergency light LED strip, "A" sticker (used to identify emergency lights). When ordering luminaires by Lighting Technologies with the emergency lighting solution, specify the luminaire part number followed by EM

Installation

Installed in the luminaire housing.

Design

Emergency lighting testing and control are performed from a TELEMANDO device.



Dimensional characteristics

A	Length	170 mm
B	Width	33 mm
C	Height	28 mm
D	Length (mounting)	163 mm
	Weight	0.5 kg

Technical features

1	Article no.	6501000520
2	Power compatibility	5 W
3	Rated voltage	230 V
4	Autonomy in emergency mode	1
5	Battery Ni-Cd	RB 6,0 V 1,5 A*h Ni-Cd
6	Ambient temperature	-
7	Warranty	36 months
8	Emerg. work type	non maintained
9	Electromagnetic compatibility (EMC)	Yes
10	Climate application	-
11	Housing color	-
12	Electrical shock protection	-