

INFINITY INDIRECT MOD 1 4000K

Surface-mounted LED modular system



Description

Ceiling light system of the reflected light. Luminaire housing – sheet steel, painted with white paint. The diffuser is made of opal acrylic glass. The system is available in the form designer, and in the form of finished shapes. To create and see your own modular designs, visit the application infinity.designer at www.lucis.eu.

Installation

Mounted on a wall or ceiling.

Design

Body of luminaire are plate irons painted white. Diffuser is made of opal acrylic glass.

Optical part

Opal diffuser



Dimensional characteristics

A	Length	510 mm
B	Width	120 mm
C	Height	32 mm
	Weight	0.9 kg

Technical features

1	Article no.	1362000250
2	Light source	OLED
3	Luminous flux	2150 lm
4	Power compatibility	14 W
5	Energy efficiency	154 lm/W
6	Color rendering index (CRI)	>80
7	Color temperature	4000 K
8	Power factor (cosFI)	> 0,90
9	Alternating/direct current (AC/DC)	No
10	Dimming	-
11	Rated voltage	230 V
12	Electrical shock protection	I
13	Electromagnetic compatibility (EMC)	No
14	Climate application	Clm App4
15	Ambient temperature	+5 to +35 C
16	Housing color	White
17	Fire protection class	III
18	Flickering	<5%
19	Ingress protection (IP)	IP20
20	Mechanical shock protection	IK02/0,2 J
21	Energy efficiency class	A++
22	Inrush current	-
23	Inrush current impulse time	0 µs
24	Emergency power supply unit	No
25	Beam angle	D120
26	Warranty	60 months
27	Autonomy in emergency mode	-
28	Light flux in emergency mode	-
29	Color of light	Белый