

LYRA 6500-4 LED

LYRA series luminaires

Description

Lightweight and reliable light sign with a decorative aluminum frame. Universal solution with 30 m recognition distance. The IP65, centrally operated versions work at low down to $-30\text{ }^{\circ}\text{C}$ (parking lots).

Installation




Mounted on a wall or ceiling.

Design

Polycarbonate housing. An operational status LED is installed on the housing panel. Emergency lighting testing and control are performed from a TELEMANDO device. Rechargeable batteries are included.

Optical part

Polycarbonate diffuser. Pictograms are supplied separately. Recognition distance 30 m. LED lamps are included.



Dimensional characteristics

A	Length	342 mm
B	Width	158 mm
C	Height	74 mm
D	Length (mounting)	250 mm
	Weight	0.9 kg

Technical features

1	Article no.	4502002330
2	Light source	LED
3	Power compatibility	4 W
4	Power factor (cosFI)	> 0,50
5	Emergency power supply unit	No
6	Energy efficiency class	A
7	Color rendering index (CRI)	>70
8	Flickering	<5%
9	Luminous flux	200 lm
10	Battery Ni-Cd	No accumulator
11	Rated voltage	230 V
12	Electrical shock protection	II
13	Ambient temperature	-30 to +40 C
14	Climate application	CIm App4
15	Housing color	White
16	Fire protection class	-
17	Electromagnetic compatibility (EMC)	Yes
18	Ingress protection (IP)	IP65
19	Mechanical shock protection	IK02/0,2 J
20	Alternating/direct current (AC/DC)	Yes
21	Autonomy in emergency mode	-
22	Emerg. work type	central battery
23	Average brightness	300
24	Identification distance	31
25	Warranty	60 months
26	Light flux in emergency mode	200 lm