

## OKKO P 26 BL 4000K

Suspended LED downlight

### Description

Suspended LED downlight. The luminaire body is made of aluminum, painted matt paint. Deep mirror decorative frame of mirrored aluminum creates a large protective angle and effect of the "turn off" the light source – "dark light". Optical part closed faceted glass. WH Standard color – white.

### Installation


Suspended to a ceiling.

### Design

The body is made of aluminium and painted matte white. Deep decorative frame made from aluminium with mirror surface. Optical part closed by the matt glass.

### Optical part

Diffuser is frosted glass



## Dimensional characteristics

A	Diameter	180 mm
C	Height	236 mm
	Weight	1.3 kg

## Technical features

1	Article no.	1235000540
2	Light source	LED
3	Luminous flux	3200 lm
4	Power compatibility	29 W
5	Energy efficiency	110 lm/W
6	Color rendering index (CRI)	>80
7	Color temperature	4000 K
8	Power factor (cosFI)	> 0,90
9	Alternating/direct current (AC/DC)	No
10	Dimming	-
11	Rated voltage	230 V
12	Electrical shock protection	I
13	Electromagnetic compatibility (EMC)	No
14	Climate application	Clm App4
15	Ambient temperature	0 to +40 C
16	Housing color	Black
17	Fire protection class	III
18	Flickering	<5%
19	Ingress protection (IP)	IP20
20	Mechanical shock protection	IK02/0,2 J
21	Energy efficiency class	A+
22	Inrush current	60 A
23	Inrush current impulse time	400 µs
24	Emergency power supply unit	No
25	Beam angle	D70
26	Warranty	60 months
27	Autonomy in emergency mode	-
28	Light flux in emergency mode	-