

OKKO S 38 BL 3000K

Surface mounted ceiling LED downlight

Description


Surface mounted ceiling LED downlight. The luminaire body is made of aluminum, painted matt paint. Deep mirror decorative frame of mirrored aluminum creates a large protective angle and effect of the "turn off" the light source – "dark light". Optical part closed faceted glass. WH Standard color – white.

Installation

Mounted on a wall or ceiling.

Design

The body is made of aluminium and painted matte white. Deep decorative frame made from aluminium with mirror surface. Optical part closed by the matt glass.



Dimensional characteristics

A	Diameter	230 mm
C	Height	281 mm
	Weight	2 kg

Technical features

1	Article no.	1235000850
2	Light source	LED
3	Luminous flux	3800 lm
4	Power compatibility	41 W
5	Energy efficiency	93 lm/W
6	Color rendering index (CRI)	>80
7	Color temperature	3000 K
8	Power factor (cosFI)	> 0,97
9	Alternating/direct current (AC/DC)	No
10	Dimming	-
11	Rated voltage	230 V
12	Electrical shock protection	I
13	Electromagnetic compatibility (EMC)	No
14	Climate application	Clm App4
15	Ambient temperature	0 to +40 C
16	Housing color	Black
17	Fire protection class	III
18	Flickering	<5%
19	Ingress protection (IP)	IP20
20	Mechanical shock protection	IK02/0,2 J
21	Energy efficiency class	A+
22	Inrush current	60 A
23	Inrush current impulse time	300 µs
24	Emergency power supply unit	No
25	Beam angle	D70
26	Warranty	60 months
27	Autonomy in emergency mode	-
28	Light flux in emergency mode	-