

RONDO S 550 WH LED 4000K

Surface-mounted glass LED luminaire



Description

Ceiling or wall surface mounted luminaire creates diffused illumination. Diffuser made of hand blown three-layered opal glass. Mounting plate made of metal painted matte white.

Installation



On a ceiling.

Design

Extra slim hand-blown three-ply opal glass diffuser. The diffuser is attached to a metal plate using special latches. Control gear is installed on the plate.

Optical part

Opal diffuser.



Dimensional characteristics

A	Diameter	550 mm
C	Height	76 mm
D	Diameter (mounting)	342 mm
	Weight	6 kg

Technical features

1	Article no.	1467000040
2	Light source	LED
3	Luminous flux	2950 lm
4	Power compatibility	32 W
5	Energy efficiency	92 lm/W
6	Color rendering index (CRI)	>80
7	Color temperature	4000 K
8	Power factor (cosFI)	> 0,95
9	Alternating/direct current (AC/DC)	No
10	Dimming	-
11	Rated voltage	230 V
12	Electrical shock protection	I
13	Electromagnetic compatibility (EMC)	Yes
14	Climate application	Clim App4
15	Ambient temperature	+5 to +35 C
16	Housing color	White
17	Fire protection class	III
18	Flickering	<5%
19	Ingress protection (IP)	IP40
20	Mechanical shock protection	IK02/0,2 J
21	Energy efficiency class	A+
22	Inrush current	20 A
23	Inrush current impulse time	108 µs
24	Emergency power supply unit	No
25	Beam angle	D120
26	Warranty	60 months
27	Autonomy in emergency mode	-
28	Light flux in emergency mode	-