

LINER/S DR LED

Suspended light lines

Description

Suspended modular LED-based lighting system for offices, meeting rooms, corridors, lobbies, and lounges. Modern design, comfortable light, and energy efficiency – these are unbeatable arguments for choosing the Liner LED. Line width 10 cm.

Installation

Mounted on the ceiling surface using the included wire-rope suspensions (max. 2 m). LINER DR luminaires are designed to be connected in-line. For in-line connection, an end cap kit needs to be ordered that includes 2 end caps and the associated fasteners. Order codes for LINER/S DR LED end cap kits: 2471000090 (white), 2471000100 (metallic). LINER/S CC LED is an angled unit.

Design

White or metallic powder-painted aluminium profile housing.

Optical part

Opal PMMA diffuser. LED type: SMD.

Usage

Cultural and entertainment facilities

Educational institutions

HoReCa / hotels / restaurants / cafes

Housing and public utilities

Mall

Medical institutions

Meeting rooms


Office and administrative premises

Stairs / hallways

Transport hubs (railway stations, airports)



LINER/S CC LED



Models list

Title	Luminous flux	Power Capability	lm/W	Length	Width	Weight	Article no.
LINER/S DR LED 1500 W 4000K /E/	2850 lm	33 W	86	1425 mm	105 mm	5.300 kg	1997017380
LINER/S DR LED 1500 S 4000K /E/	2850 lm	33 W	86	1425 mm	105 mm	5.300 kg	1997017370
LINER/S DR LED 1200 W 4000K /E/	2200 lm	26 W	85	1140 mm	105 mm	4.400 kg	1997017360
LINER/S DR LED 1200 S 4000K /E/	2200 lm	26 W	85	1140 mm	105 mm	4.400 kg	1997017330