

## LINER/S DR LED

Suspended light lines



### Description

Suspended modular LED-based lighting system for offices, meeting rooms, corridors, lobbies, and lounges. Modern design, comfortable light, and energy efficiency – these are unbeatable arguments for choosing the Liner LED. Line width 10 cm.

### Installation

Mounted on the ceiling surface using the included wire-rope suspensions (max. 2 m). LINER DR luminaires are designed to be connected in-line. For in-line connection, an end cap kit needs to be ordered that includes 2 end caps and the associated fasteners. Order codes for LINER/S DR LED end cap kits: 2471000090 (white), 2471000100 (metallic). LINER/S CC LED is an angled unit.

### Design

White or metallic powder-painted aluminium profile housing.

### Optical part

Opal PMMA diffuser. LED type: SMD.

### Usage

Cultural and entertainment facilities

Educational institutions

HoReCa / hotels / restaurants / cafes

Housing and public utilities

Mall

Medical institutions

Meeting rooms

Office and administrative premises

Stairs / hallways

Transport hubs (railway stations, airports)



**Models list**

<b>Title</b>	<b>Luminous flux</b>	<b>Power Capability</b>	<b>lm/W</b>	<b>Length</b>	<b>Height</b>	<b>Width</b>	<b>Weight</b>	<b>Article no.</b>
LINER/S DR LED 1500 W 4000K /E/	2800.00 lm	32.00 W	88.00	1425 mm	94 mm	105 mm	5.30 kg	1997017380
LINER/S DR LED 1500 S 4000K /E/	2800.00 lm	32.00 W	88.00	1425 mm	94 mm	105 mm	5.30 kg	1997017370
LINER/S DR LED 1200 S 4000K /E/	2200.00 lm	26.00 W	85.00	1140 mm	94 mm	105 mm	4.40 kg	1997017330
LINER/S DR LED 1200 W 4000K /E/	2200.00 lm	26.00 W	85.00	1140 mm	94 mm	105 mm	4.40 kg	1997017360