

MAGISTRAL LED

Effective lighting solution of highway



Description

Modern design, high efficiency, special optic system and convenient maintenance solution makes this luminaire best choice for highways and overhead roads.

Installation

The luminaire can be mounted on outer support as well as on 48-60 mm pole post. Tilt angle is adjustable up to minus 15 degrees with 5 degree intervals

Design

Housing and universal adjustable mounting fixture made of die-cast aluminum. A driver is installed inside the housing.

Optical part

Complex cluster-type optics with a wide lateral and axial light distribution. Protective tempered silicate glass diffuser. LED type: SMD.

Usage

Car Park / Parking

Road lighting



Models list

Title	Luminous flux	Power Capability	lm/W	Length	Height	Width	Weight	Article no.
MAGISTRAL LED 300 (SW) 4000K /E/	39500.00 lm	288.00 W	137.00	956 mm	188 mm	410 mm	16.00 kg	1997024760
MAGISTRAL LED 150 (SW) 4000K /E/	21500.00 lm	156.00 W	138.00	956 mm	188 mm	410 mm	16.00 kg	1997024290
MAGISTRAL LED 300 (W) 4000K /E/	39500.00 lm	288.00 W	137.00	956 mm	188 mm	410 mm	16.00 kg	1997024770
MAGISTRAL LED 240 (W) 4000K /E/	29500.00 lm	211.00 W	140.00	956 mm	188 mm	410 mm	16.00 kg	1997024750
MAGISTRAL LED 240 (SW) 4000K /E/	29500.00 lm	211.00 W	140.00	956 mm	188 mm	410 mm	16.00 kg	1997024740
MAGISTRAL LED 150 (SW) 5000K /E/	20200.00 lm	156.00 W	129.00	956 mm	188 mm	410 mm	16.00 kg	1997029230
MAGISTRAL LED 150 (W) 4000K /E/	21500.00 lm	156.00 W	138.00	956 mm	188 mm	410 mm	16.00 kg	1997024730