

OWP

IP54 rated luminaires

Description

Surface-mounted luminaire for clean rooms and healthcare facilities. Can be used in various applications with special requirements regarding the maximum concentration of suspended particulate matter thanks to the high IP54 ingress protection rating.

Installation

Installed recessed in Armstrong type suspended ceilings or mounted on the ceiling surface.

Design

White powder-painted weld sheet steel housing. Control gear is installed inside the housing. A silicone seal is attached along the perimeter.

Optical part



OWP 255: specular parabolic louver made of anodized aluminum. Clear silicate tempered glass, attached to the housing with screws. OWP 336: opal PMMA diffuser made in a metal frame secured in the housing with screws. Can be optionally supplied with a matte tempered silicate glass.

Usage

Clean room

Industrial enterprises

Medical institutions



Models list

Title	Number of Lamps	Power Capability	Ballast	Socle	Lamp Type	Length	Width	Article no.
OWP 336 /595/ IP54/IP54 HF mat	3	108 W	ECG	2G11	CFL	595 mm	595 mm	1371000100
OWP 336 /595/ IP54/IP54 HF	3	108 W	ECG	2G11	CFL	595 mm	595 mm	1371000090
OWP 336 /595/ IP54/IP54	3	108 W	EmCG	2G11	CFL	595 mm	595 mm	1371000070
OWP 336 /595/ IP54/IP54 mat	3	108 W	EmCG	2G11	CFL	595 mm	595 mm	1371000120
OWP 255 /595/ IP54/IP54	2	110 W	ECG	2G11	CFL	595 mm	595 mm	1371000020
OWP 255 /595/ IP54/IP54 ES1	2	110 W	ECG	2G11	CFL	595 mm	595 mm	1371000030
OWP 336 /595/ IP54/IP54 ES1	3	108 W	EmCG	2G11	CFL	595 mm	595 mm	1371000080