

PRS/R ECO LED

ECO series luminaires

Description

Recessed LED-based luminaire for offices and classrooms with uniform shadowless diffuser illumination and high luminous efficacy (up to 112 lm/W).

Installation

Installed recessed in Armstrong type suspended ceilings or plasterboard ceilings using mounting clips. Order code for clips: 2905000110

Design

White powder-painted weld sheet steel housing. Control gear is installed inside the housing.

Optical part

ECO LED module provides uniform shadowless illumination of luminaire diffuser. Diffuser made of transparent polymeric material with prismatic structure in metal frame. LED type: SMD.

Usage

Cultural and entertainment facilities

Educational institutions

HoReCa / hotels / restaurants / cafes


Housing and public utilities

Mall

Medical institutions

Office and administrative premises

Transport hubs (railway stations, airports)



Models list

Title	Luminous flux	Power Capability	lm/W	Length	Width	Weight	Article no.
PRS/R ECO LED 595 4000K /E/	4000 lm	32 W	125	595 mm	595 mm	4.500 kg	1997018080
PRS/R ECO LED 620 4000K /E/	4000 lm	32 W	125	620 mm	624 mm	4.700 kg	1997012880
PRS/R ECO LED 300 4000K /E/	1800 lm	18 W	100	595 mm	295 mm	2.800 kg	1997018070
PRS/R ECO LED 595 4000K ARMSTRONG /E/	4000 lm	32 W	125	591 mm	591 mm	3.800 kg	1997024580
PRS/R ECO LED 595 5000K /E/	4100 lm	32 W	128	595 mm	595 mm	4.500 kg	1997020280
PRS/R ECO LED 1200 4000K /E/	3700 lm	33 W	112	1195 mm	295 mm	5.000 kg	1997013390
PRS/R ECO LED 595 HFD 4000K /E/	4000 lm	32 W	125	595 mm	595 mm	5.250 kg	1997023350